



Note: The A&Z (H) in the name means: A(H) and Z(H).

ITEM	NAME OF PART	MATERIAL	NOTES
3	Pin header	Brass	SnCe
2	Screw	Steel	NI plated
1	Housing	PA66	UL94V-0

UL Standard:			
额定电压/电流/Rated Voltage (V)/Current (A)	B	C	D
工频耐压/Withstand Voltage	300V/10	/	300/10
绝缘电阻/Insulation Resistance	A<math>2000V/1Min</math>		
螺丝扭矩/Torque Tightening (N · m/lb.in)	500V/2/DN<math>300V</math>		
线径范围/导线规格 (AWG)	N2.5, 0.4/0.54		
间距/Pitch (mm)/线数范围/Poles	22~16		
使用温度范围/Operating temperature (°C)	6.35/N=0~25P		
符合 RoHS 环保要求/Conform to RoHS	-40~+105		
标准颜色编号/Standard color number: PANTONE /RAL	Yes		

<b>DEGSON</b>	
APPR: 核准人	核准日期
CMO: 审核人	审核日期
DRT: 设计人	设计日期
MM: 物料号	物料规格
MAT NO. /REV: /	MAT STATUS: /
SURFACE/COLOR: /	

00	/	/	/	/	REV	EON	DESCRIPTION	DRT	DATE	DRT	DATE	DRWING NO.	TYPE	DRWING STATUS	SCALE	SHEET
							DG16R-B-XXP-1Y-00A&Z (H)					200058786	CUSTOMER DRAWING	/	2:1	1/1

1 2 3 4 5 6