



公差/General tolerances(mm)		0.1/10
0	>3	~
3	>6	~
6	>10	~
10	>18	~
18	>30	~
30	>50	~
50	>80	~
80	>120	~
120	>180	~
180	>250	~
250	>315	~
315	>400	~
400	>500	~
500	>500	~
±0.12/±0.18/±0.22/±0.26/±0.31/±0.37/±0.57/±0.80/±0.93/±1.05/±1.15/±1.50/±2.20/±2.50		±7

ITEM	NAME OF PART	MATERIAL	NOTES
5	Nut	Copper Alloy	M2.5
4	Short Pin	Copper	Sn plated
3	Long Pin	Copper	Sn plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL Standard:		B	C	D
额定电压/电压/Rated Voltage(V)	Current(A)	300/15	/	300/10
IEC 标准/EC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree	额定电压/电压/Rated Voltage(V)	Current(A)	320/10	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	额定脉冲电压(KV)/Rate Impulse Voltage(KV)		4	/
间距/Pitch(mm)	线数范围/Poles		5.08/N=04~44P	
使用温度范围/Operating temperature(°C)			-40~+105	
符合RoHS环保要求/Conform to RoHS				



APPR:	2024.04.09	NAME	MAT NO./REV:	00	SURFACE/COLOR:	批号
CHDR:	姜耀志	2024.04.01				
DRAWING NO. <td>200019534 <td>TYPE <td colspan="4">ZEDGRHM-5-08-XXP-1Y-00A&Z(H)</td> </td></td>	200019534 <td>TYPE <td colspan="4">ZEDGRHM-5-08-XXP-1Y-00A&Z(H)</td> </td>	TYPE <td colspan="4">ZEDGRHM-5-08-XXP-1Y-00A&Z(H)</td>	ZEDGRHM-5-08-XXP-1Y-00A&Z(H)			
DRFT:	方哲建	2024.04.01				
DATE	2024.04.01	DRAWING STATUS	已发布			
DESCRIPTION	1X 到 50 脚 电压 320V 电流 10A	SCALE	2:1			
REV	01	SHEET	1/1			

REV	ECN	DESCRIPTION	DRFT	DATE
01		1X 到 50 脚 电压 320V 电流 10A	方哲建	2024.04.01

1 2 3 4 5 6